

CARE AND MAINTENANCE INSTRUCTIONS

Wood



Material Characteristics

The wood finishes are crafted using a water-based mixed painting process on birch plywood panels, veneered in oak and walnut, with AW 100 bonding for humid environments.

The edge banding is done with water-resistant polyurethane adhesives. All panels are classified as E1 and, upon request, CARB2 for low formaldehyde emission.

For particularly dirty areas or stubborn stains, please contact our Falper Customer Care at customercare@falper.it or FILA technical support at info@filasolutions.com.

CARE AND MAINTENANCE INSTRUCTIONS

Wood

To always keep the surface in the best condition, it is recommended to pay particular attention to the maintenance phases of the artifact.

Recommendations:

- Use FILA SPLENDIWOOD to revitalize the wood. Spray it on a clean, damp cloth and wipe the surface to be cleaned. The product dries quickly, and no rinsing is necessary.
- Use FILA POWER DEGREASER to remove stubborn and greasy dirt.
- For surfaces with normal or intense dirt, spray directly onto the surface, let it act, and then rinse with a damp cloth or sponge.

Not recommended:

- Do not use abrasive sponges.
- Do not use wood cleaning products that can damage the matte finish.

CAUTION: Absolutely avoid detergents containing ammonia and/or solvents and ethyl alcohol, regardless of their concentration and even if diluted, as they can attack the material. Do not use excessively abrasive tools. Avoid rough and abrasive sponges, metallic scrubbers. Coffee and tea can permanently stain the product.

For particularly dirty areas or stubborn stains, please contact our Falper Customer Care at customercare@falper.it or FILA technical support at info@filasolutions.com.